



H
08




GROUP - 08

PLASTIC AND METAL KNURLED HANDWHEELS

BOTECO Plastic and Metal Knurled Handwheels

Range of handwheels with marked knurling on the outer rim of the knob, designed to offer excellent grip even when held with fingertips. Available in plastic and metal (steel, stainless steel, aluminium). These handwheels allow users to exert a certain tightening force despite being small in size and often used in tight spaces. Boteco offers various solutions both in terms of dimensions and size of the studs and inserts with threaded hole. For detailed information on the specifications of each individual product please consult the technical sheet.



H171

KNURLEDHANDWHEEL WITH SHORT HUB



Materials:

Reinforced polyamide.
Resistant to oils and greases.

Surface finish:

Satin.

Colour:

Black (RAL9011).

Inserts:

H171:

Galvanised steel threaded stud (thread tolerance 6g).



H171CON:

Brass insert with female threaded hole (thread tolerance 6H).

Special requests:

- Upon request and for special quantities inserts with stud can be supplied with customised lengths for a minimum quantity of 100 pieces.

08



Version H171CON: With brass insert.

Code	art.	D	H	d	m	c	d1 _{6H}	g
H17125.0002	H17125.TM0601CON	25	12	15.5	4	8	M6	7
H17125.0015	H17125.TM0801CON	25	12	15.5	4	8	M6	8

Version H171: With galvanised steel stud.

Code	art.	D	H	d	m	c	LM	d1 _{6g}	Q	g
H17125.0006	H17125.TM06X2001	25	12	15.5	4	8	40	M6	20	11
H17125.0019	H17125.TM08X2001	25	12	15.5	4	8	40	M8	20	15

LM = maximum mouldable length.

Customised stud length available for a minimum of 250 pieces.



H172

KNURLEDKNOB WITH SLOT END AND THREADED STUD





Materials:
Reinforced polyamide.
Resistant to oils and greases.
Surface finish:
Satin.

Colour:
Black (RAL9011).

Inserts:
Galvanisedsteelthreaded stud (thread tolerance 6g).

- Special Requests:**
- Upon request and for special quantities inserts can be supplied with customised lengths.
 - Upon request and for special quantities inserts can be supplied in different materials.
 - Upon request and for special quantities available in the colours indicated in the chart [page].



Code	art.	D	H	d	m	c	A	B	LM	d1 _{6g}	Q	g
H17220.0003	H17220.TM06X1501	20	8	13,5	1	7	14	2,5	39	M6	15	7

LM = maximum mouldable length.
Threaded stud length on request, with a minimum quantity of 250 pieces.



H180

KNURLEDKNOB WITH BAKELITE HUB AND THREADED HOLE INSERT



Materials:

Phenolic resin.

Resistant to oils and greases.

Resistant to high temperatures.

Surface finish:

Glossy.

Colour:

Black (RAL9011).

Inserts:


Brass insert with female threaded hole (thread tolerance 6H).

Special requests:

- None.



08



Code	art.	D	H	d	d1 _{6H}	Q	g
H18015.0001	H18015.BM0501	15	18	11	M5	11	5



BOTECA

335 ()

H753

KNURLED SOLID HANDWHEEL WITH THREADED STUD



Materials:

Reinforced polyamide.
Resistant to oils and greases.

Surface finish:

Satin.

Colour:

Black (RAL9011).

Inserts:


Galvanised steel threaded stud (thread tolerance 6g).

Special Requests:

- Upon request and for special quantities inserts can be supplied with customised lengths.
- Upon request and for special quantities inserts can be supplied in different materials.
- Upon request and for special quantities available in the colours indicated in the chart [page].



08



Code	art.	D	H	d	m	c	d2	LM	d1 _{6g}	Q	g
H75326.0004	H75326.TM05X2001	26	18	16	8.5	9.5	12	50	M5	20	10
H75326.0008	H75326.TM06X2001	26	18	16	8.5	9.5	12	50	M6	20	13
H75326.0009	H75326.TM06X2501	26	18	16	8.5	9.5	12	50	M6	25	14
H75326.0012	H75326.TM08X2001	26	18	16	8.5	9.5	12	50	M8	20	20
H75 326 . 0 014	H75 326 . T M 0 8 X 3 0 01	26	18	16	8.5	9.5	12	50	M8	30	22

LM = maximum mouldable length.

Threaded stud length on request, with a minimum quantity of 250 pieces.



H757

KNURLED SOLID HANDWHEEL WITH FEMALE THREADED INSERT




Materials:
Reinforced polyamide.
Resistant to oils and greases.
Surface finish:
Satin.

Colour:
Black (RAL9011).
Inserts:

Brass insert with female threaded hole (thread tolerance 6H).

Special Requests:

- Upon request and for special quantities inserts can be supplied in different materials.
- Upon request and for special quantities available in the colours indicated in the chart [page.].



Code	art.	D	H	d	m	c	d2	d1 _{6H}	Q	
H75726.0007	H75726.TM0501	26	18	16	8.5	9.5	12	M5	6	9
H75726.0008	H75726.TM0601	26	18	16	8.5	9.5	12	M6	8	10
H75726.0009	H75726.TM0801	26	18	16	8.5	9.5	12	M8	8	11

H758

KNURLEDHANDWHEEL WITH HUB AND FEMALE THREADED INSERT



Materials:

Reinforced polyamide.
Resistant to oils and greases.

Surface finish:

Satin.

Colour:

Black (RAL9011).

Inserts:


Brassinsertwithfemale threaded hole (thread tolerance 6H).

Special Requests:

- Upon request and for special quantities inserts can be supplied in different materials.
- Upon request and for special quantities available in the colours indicated in the chart [page].



08



Code	art.	D	H	d	m	c	d1 _{6H}	Q	g
H75815.0002	H75815.TM0401	15	11,5	10,5	4	7,5	M4	7	4
H75815.0005	H75815.TM0501	15	11,5	10,5	4	7,5	M5	7	4
H75815.0010	H75815.TM0601	15	11,5	10,5	4	7,5	M6	7	4



BATECO

H759

KNURLEDHANDWHEEL WITH HUB AND THREADED STUD




Materials:
Reinforced polyamide.
Resistant to oils and greases.
Surface finish:
Satin.

Colour:
Black (RAL9011).
Inserts:

Galvanisedsteelthreaded stud (thread tolerance 6g).

Special Requests:

- Upon request and for special quantities inserts can be supplied with customised lengths.
- Upon request and for special quantities inserts can be supplied in different materials.
- Upon request and for special quantities available in the colours indicated in the chart [page].



Code	art.	D	H	d	m	c	LM	d1 _{6g}	Q	
-	H75915.TM03X1101	15	11,5	10,5	4	7,5	70	M3	11	3
-	H75915.TM03X2401	15	11,5	10,5	4	7,5	70	M3	24	3,5
-	H75915.TM04X1001	15	11,5	10,5	4	7,5	70	M4	10	3,5
-	H75915.TM04X2001	15	11,5	10,5	4	7,5	70	M4	20	4
-	H75915.TM04X3001	15	11,5	10,5	4	7,5	70	M4	30	4,5
-	H75915.TM05X1001	15	11,5	10,5	4	7,5	70	M5	10	4
-	H75915.TM05X1601	15	11,5	10,5	4	7,5	70	M5	16	4,5
-	H75915.TM05X2001	15	11,5	10,5	4	7,5	70	M5	20	5,5
-	H75915.TM05X3001	15	11,5	10,5	4	7,5	70	M5	30	6,5
-	H75915.TM06X1001	15	11,5	10,5	4	7,5	70	M6	10	5
-	H7591 5 . T M 0 6 X 16 0 1	15	11,5	10,5	4	7,5	70	M6	16	6
-	H75915.TM06X2001	15	11,5	10,5	4	7,5	70	M6	20	7,5

LM = maximum mouldable length.
Threaded stud length on request, with a minimum quantity of 250 pieces.

H760

KNURLEDHANDWHEEL WITH THREADED STUD




Materials:
Reinforced polyamide.
Resistant to oils and greases.
Surface finish:
Satin.

Colour:
Black (RAL9011).

Inserts:
Galvanisedsteelthreaded stud (thread tolerance 6g).

Special Requests:

- Upon request and for special quantities inserts can be supplied with customised lengths.
- Upon request and for special quantities inserts can be supplied in different materials.
- Upon request and for special quantities available in the colours indicated in the chart [page].



Code	art.	D	H	LM	d1 _{6g}	Q	g
H76015.0004	H76015.TM04X1301	15	8	77	M4	13	2
H76015.0005	H76015.TM04X1501	15	8	77	M4	15	2
H76015.0009	H76015.TM04X1901	15	8	77	M4	19	2,5
H76015.0012	H76015.TM04X2401	15	8	77	M4	24	3
H76015.0021	H76015.TM05X1501	15	8	77	M5	15	4
H76015.0026	H76015.TM05X1901	15	8	77	M5	19	4,5
H76015.0027	H76015.TM05X2401	15	8	77	M5	24	5
H76015.0029	H76015.TM05X2901	15	8	77	M5	29	5,5
H76015.0035	H76015.TM06X1501	15	8	77	M6	15	5,5
H76015.0039	H76015.TM06X1901	15	8	77	M6	19	6,5
H76015.0042	H76015.TM06X2401	15	8	77	M6	24	7
H76015.0043	H76015.TM06X2901	15	8	77	M6	29	7,5

LM = maximum mouldable length.
Threaded stud length on request, with a minimum quantity of 250 pieces.

H765

KNURLED HOLLOW HANDWHEEL WITH THREADED THROUGH-HOLE INSERT

Materials:

Reinforced polyamide.

Resistant to oils and greases.

Surface finish:

Satin.

Colour:

Black

Inserts: (RAL9011).

H765:


Brass insert with threaded through hole (thread tolerance 6H).

H765PIN:

Stainless steel insert with threaded through hole (Aisi 303) (thread tolerance 6H).

Special Requests:

- Upon request and for special quantities available in the colours indicated in the chart [page.].



Version H765: brass insert.

Code	art.	D	H	d	m	c	d2	d3	d4	h3	d1 _{6H}	Q	g
H76515.0002	H76515.TM0401	15	10.5	10	4.5	6	8	10	7.5	2	M4	8.5	2
H76515.0006	H76515.TM0501	15	10.5	10	4.5	6	8	10	7.5	2	M5	8.5	2
H76521.0002	H76521.TM0501	21	15	13	6.5	8.5	9.5	15	10.5	2.5	M5	12.5	5
H76521.0006	H76521.TM0601	21	15	13	6.5	8.5	9.5	15	10.5	2.5	M6	12.5	5
H76526.0002	H76526.TM0601	26	18	16	8.5	9.5	12	19	13	3	M6	15	10
H76526.0004	H76526.TM0801	26	18	16	8.5	9.5	12	19	13	3	M8	15	10
H76533.0002	H76533.TM0801	32	23	20	10.5	12.5	15	23	16	5	M8	18	16
H76533.0004	H76533.TM1001	32	23	20	10.5	12.5	15	23	16	5	M10	18	16
H76540.0002	H76540.TM0801	40	28	25	12.5	15.5	18	29	20.5	6	M8	22	31
H76540.0004	H76540.TM1001	40	28	25	12.5	15.5	18	29	20.5	6	M10	22	32
H76540.0006	H76540.TM1201	40	28	25	12.5	15.5	18	29	20.5	6	M12	22	32
H76540.0008	H76540.TM1401	40	28	25	12.5	15.5	18	29	20.5	6	M14	22	34

Version H765PIN: stainless steel insert Aisi 303.

INOX

Code	art.	D	H	d	m	c	d2	d3	d4	h3	d1 _{6H}	Q	g
H76515.0003	H76515.TM0401PIN	15	10.5	10	4.5	6	8	10	7.5	2	M4	8.5	3
H76515.0007	H76515.TM0501PIN	15	10.5	10	4.5	6	8	10	7.5	2	M5	8.5	3
H76521.0003	H76521.TM0501PIN	21	15	13	6.5	8.5	9.5	15	10.5	2.5	M5	12.5	6
H76521.0007	H76521.TM0601PIN	21	15	13	6.5	8.5	9.5	15	10.5	2.5	M6	12.5	6
H76526.0003	H76526.TM0601PIN	26	18	16	8.5	9.5	12	19	13	3	M6	15	11.5
H76526.0005	H76526.TM0801PIN	26	18	16	8.5	9.5	12	19	13	3	M8	15	11.5
H76533.0003	H76533.TM0801PIN	32	23	20	10.5	12.5	15	23	16	5	M8	18	18
H76533.0005	H76533.TM1001PIN	32	23	20	10.5	12.5	15	23	16	5	M10	18	18
H76540.0003	H76540.TM0801PIN	40	28	25	12.5	15.5	18	29	20.5	6	M8	22	32
H76540.0005	H76540.TM1001PIN	40	28	25	12.5	15.5	18	29	20.5	6	M10	22	31
H76540.0007	H76540.TM1201PIN	40	28	25	12.5	15.5	18	29	20.5	6	M12	22	34

H766

KNURLED HOLLOW HANDWHEEL WITH THREADED STUD



PA6
+G.F.



Materials:

Reinforced polyamide.
Resistant to oils and greases.

Surface finish:

Satin.

Colour:


Black (RAL9011).

Inserts:

Galvanised steel threaded stud (thread tolerance 6g).

Special Requests:

- Upon request and for special quantities inserts can be supplied with customised lengths.
- Upon request and for special quantities inserts can be supplied in different materials.
- Upon request and for special quantities available in the colours indicated in the chart [page.].



Code	art.	D	H	d	m	c	d2	d3	d4	h1	h3	LM	d1 _{6g}	Q	g
H76615.0001	H76615.TM04X1101	15	10.5	10	4.5	6	8	10	7.5	8.5	2	40	M4	11	2,5
H76615.0004	H76615.TM04X1501	15	10.5	10	4.5	6	8	10	7.5	8.5	2	40	M4	15	3
H76615.0007	H76615.TM04X1901	15	10.5	10	4.5	6	8	10	7.5	8.5	2	40	M4	19	3,5
H76615.0013	H76615.TM05X1101	15	10.5	10	4.5	6	8	10	7.5	8.5	2	40	M5	11	4
H76615.0016	H76615.TM05X1501	15	10.5	10	4.5	6	8	10	7.5	8.5	2	40	M5	15	4,5
H76615.0018	H76615.TM05X1901	15	10.5	10	4.5	6	8	10	7.5	8.5	2	40	M5	19	5
H76621.0003	H76621.TM05X1001	21	15	13	6.5	8.5	9.5	15	10.5	12.5	2.5	40	M5	10	6,5
H76621.0005	H76621.TM05X1601	21	15	13	6.5	8.5	9.5	15	10.5	12.5	2.5	40	M5	16	6,5
H76 621 . 0 0 07	H76621.TM05X2001	21	15	13	6.5	8.5	9.5	15	10.5	12.5	2.5	40	M5	20	7,5
H76621.0011	H76621.TM05X3001	21	15	13	6.5	8.5	9.5	15	10.5	12.5	2.5	40	M5	30	9,5
H76 621 . 0 015	H76621.TM06X1001	21	15	13	6.5	8.5	9.5	15	10.5	12.5	2.5	40	M6	10	7,5
H76621.0022	H76621.TM06X1601	21	15	13	6.5	8.5	9.5	15	10.5	12.5	2.5	40	M6	16	8,5
H76 621 . 0 0 24	H76621.TM06X2001	21	15	13	6.5	8.5	9.5	15	10.5	12.5	2.5	40	M6	20	9
H76 621 . 0 0 29	H76621.TM06X2501	21	15	13	6.5	8.5	9.5	15	10.5	12.5	2.5	40	M6	25	10,5
H76626.0002	H76626.TM06X1001	26	18	16	8.5	9.5	12	19	13	15	3	80	M6	10	10
H76626.0006	H76626.TM06X1601	26	18	16	8.5	9.5	12	19	13	15	3	80	M6	16	11
H76626.0009	H76626.TM06X2001	26	18	16	8.5	9.5	12	19	13	15	3	80	M6	20	11,5
H76 626 . 0 012	H76626.TM06X2501	26	18	16	8.5	9.5	12	19	13	15	3	80	M6	25	12,5
H76626.0029	H76626.TM08X1601	26	18	16	8.5	9.5	12	19	13	15	3	80	M8	16	15,5
H76 626 . 0 0 31	H76626.TM08X2001	26	18	16	8.5	9.5	12	19	13	15	3	80	M8	20	16,5
H76626.0034	H76626.TM08X2501	26	18	16	8.5	9.5	12	19	13	15	3	80	M8	25	18,5
H76633.0005	H76633.TM08X1601	32	23	20	10.5	12.5	15	23	16	18	5	80	M8	16	21
H76633.0008	H76633.TM08X2001	32	23	20	10.5	12.5	15	23	16	18	5	80	M8	20	24
H76633.0013	H76633.TM08X3001	32	23	20	10.5	12.5	15	23	16	18	5	80	M8	30	30
H76633.0022	H76633.TM10X2001	32	23	20	10.5	12.5	15	23	16	18	5	80	M10	20	30
H76633.0025	H76633.TM10X3001	32	23	20	10.5	12.5	15	23	16	18	5	80	M10	30	30,5
H76633.0026	H76633.TM10X4001	32	23	20	10.5	12.5	15	23	16	18	5	80	M10	40	35,5
H76640.0003	H76640.TM08X1601	40	28	25	12.5	15.5	18	29	20,5	22	6	100	M8	16	29,5
H76640.0005	H76640.TM08X3001	40	28	25	12.5	15.5	18	29	20,5	22	6	100	M8	30	38
H76640.0006	H76640.TM08X4001	40	28	25	12.5	15.5	18	29	20,5	22	6	100	M8	40	44
H76640.0011	H76640.TM10X3001	40	28	25	12.5	15.5	18	29	20,5	22	6	100	M10	30	46
H76640.0019	H76640.TM12X5001	40	28	25	12.5	15.5	18	29	20,5	22	6	100	M12	50	78

LM = maximum mouldable length.

Threaded stud length on request, with a minimum quantity of 250 pieces.



H766CIN

KNURLED HOLLOW HANDWHEEL WITH STAINLESS STEEL THREADED STUD

Materials:

Reinforced polyamide.
Resistant to oils and greases.

Surface finish:

Satin.

Colour:

Black

Inserts: (RAL9011).


Stainless steel threaded stud (Aisi 303) (thread tolerance 6g).

Special Requests:

- Upon request and for special quantities inserts can be supplied with customised lengths.
- Upon request and for special quantities available in the colours indicated in the chart [page.].



INOX



INOX

Code	art.	D	H	d	m	c	d2	d3	d4	h1	h3	LM	d1 _{6g}	Q	g
H76615.0017	H76615.TM05X1501CIN	15	10.5	10	4.5	6	8	10	7.5	8.5	2	40	M5	15	-
H76621.0006	H76621.TM05X1601CIN	21	15	13	6.5	8.5	9.5	15	10.5	12.5	2.5	40	M5	16	9.5
H76621.0019	H76621.TM06X1501CIN	21	15	13	6.5	8.5	9.5	15	10.5	12.5	2.5	40	M6	15	-
H76626.0010	H76626.TM06X2001CIN	26	18	16	8.5	9.5	12	19	13	15	3	80	M6	20	-
H76 626 . 0 0 32	H76626.TM08X2001CIN	26	18	16	8.5	9.5	12	19	13	15	3	80	M8	20	16.5
H76633.0017	H76633.TM08X4001CIN	32	23	20	10.5	12.5	15	23	16	18	5	80	M8	40	36
H76640.0009	H76640.TM10X2001CIN	40	28	25	12.5	15.5	18	29	20.5	22	6	100	M10	20	-
H76640.0018	H76640.TM12X3001CIN	40	28	25	12.5	15.5	18	29	20.5	22	6	100	M12	30	-

LM = maximum mouldable length.
Threaded stud length on request, with a minimum quantity of 250 pieces.

H767

KNURLED HOLLOW HANDWHEEL WITH FEMALE THREADED INSERT



Materials:

Reinforced polyamide.
Resistant to oils and greases.

Surface finish:

Satin.

Colour:


Black (RAL9011).

Inserts:

Brass insert with female threaded hole (thread tolerance 6H).

Special Requests:

- Upon request and for special quantities inserts can be supplied in different materials.
- Upon request and for special quantities available in the colours indicated in the chart [page.].



Code	art.	D	H	d	m	c	d2	d3	d4	h1	h3	d1 _{6H}	Q	g
H76721.0002	H76721.TM0501	21	15	13	6.5	8.5	9.5	15	10.5	12.5	2.5	M5	7	5.5
H76721.0005	H76721.TM0601	21	15	13	6.5	8.5	9.5	15	10.5	12.5	2.5	M6	7	6
H76726.0002	H76726.TM0601	26	18	16	8.5	9.5	12	19	13	15	3	M6	8	8
H76726.0005	H76726.TM0801	26	18	16	8.5	9.5	12	19	13	15	3	M8	8	8.5
H76733.0002	H76733.TM0801	32	23	20	10.5	12.5	15	23	16	18	5	M8	11	15.5
H76733.0004	H76733.TM1001	32	23	20	10.5	12.5	15	23	16	18	5	M10	10	16
H76740.0001	H76740.TM0801	40	28	25	12.5	15.5	18	29	20.5	22	6	M8	14	27
H76740.0002	H76740.TM1001	40	28	25	12.5	15.5	18	29	20.5	22	6	M10	14	28
H76740.0003	H76740.TM1201	40	28	25	12.5	15.5	18	29	20.5	22	6	M12	12	29

H770

KNURLEDKNOB WITH FEMALE THREADED INSERT



Materials:
Reinforced polyamide.
Resistant to oils and greases.
Surface finish:
Satin.


Colour:
Black (RAL9011).
Inserts:

Brassinsertwithfemale threaded hole (thread tolerance 6H).

- Special Requests:**
- Upon request and for special quantities inserts can be supplied in different materials.
 - Upon request and for special quantities available in the colours indicated in the chart [page].



08



Code	art.	D	H	d	m	c	d3	h3	d1 _{6H}	Q	
H77018.0001	H7 7018.TM 0 4 01	17.5	17.5	12	4	13.5	9	5	M4	7	5
H77018.0002	H7 7018.TM 0 5 01	17.5	17.5	12	4	13.5	9	5	M5	7	5
H77018.0003	H7 7018.TM 0 6 01	17.5	17.5	12	4	13.5	9	5	M6	7	5

H771

KNURLEDKNOB WITH THREADED STUD




Materials:
Reinforced polyamide.
Resistant to oils and greases.
Surface finish:
Satin.

Colour:
Black (RAL9011).
Inserts:

Galvanised steel threaded stud (thread tolerance 6g).

Special Requests:

- Upon request and for special quantities inserts can be supplied with customised lengths.
- Upon request and for special quantities inserts can be supplied in different materials.
- Upon request and for special quantities available in the colours indicated in the chart [page].



Code	art.	D	H	d	m	c	d3	h3	LM	d1 _{6g}	Q	g
H7 7118 . 0 0 01	H7 7118 . T M 0 4 X 10 01	17.5	17.5	12	4	13.5	9	5	50	M4	10	6
H77118.0005	H77118.TM04X1601	17.5	17.5	12	4	13.5	9	5	50	M4	16	6,5
H77118.0008	H7 7118 . T M 0 4 X 3 0 01	17.5	17.5	12	4	13.5	9	5	50	M4	30	8
H7 7118 . 0 010	H77118.TM05X1001	17.5	17.5	12	4	13.5	9	5	60	M5	10	6,5
H7 7118 . 0 012	H77118.TM05X1601	17.5	17.5	12	4	13.5	9	5	60	M5	16	7
H7 7118 . 0 013	H77118.TM05X2001	17.5	17.5	12	4	13.5	9	5	60	M5	20	8
H7 7118 . 0 0 24	H77118.TM06X1601	17.5	17.5	12	4	13.5	9	5	60	M6	16	8,5
H7 7118 . 0 0 26	H77118.TM06X2001	17.5	17.5	12	4	13.5	9	5	60	M6	20	9

LM = maximum mouldable length.
Threaded stud length on request, with a minimum quantity of 250 pieces.

H772

KNURLEDKNOB WITH THREADED THROUGH-HOLE INSERT



Materials:
 Reinforced polyamide.
 Resistant to oils and greases.
Surface finish:
 Satin.


Colour:
 Black (RAL9011).
Inserts:

Brassinsertwiththreaded through hole (thread tolerance 6H).

- Special Requests:**
- Upon request and for special quantities inserts can be supplied in different materials.
 - Upon request and for special quantities available in the colours indicated in the chart [page].



08



Code	art.	D	H	d	m	c	d3	h3	d1 _{6H}	Q	
H77218.0001	H7 7218.TM 0 4 01	17.5	17.5	12	4	13.5	9	4.5	M4	13	5.5
H77218.0002	H7 7218.TM 0 5 01	17.5	17.5	12	4	13.5	9	4.5	M5	13	5.5
H77218.0003	H7 7218.TM 0 6 01	17.5	17.5	12	4	13.5	9	4.5	M6	13	5.5

H773

KNURLEDKNOB WITH SLOT END AND FEMALE THREADED INSERT



Materials:

Reinforced polyamide.
Resistant to oils and greases.

Surface finish:

Satin.

Colour:


Black (RAL9011).

Inserts:

Brass insert with female threaded hole (thread tolerance 6H).

Special Requests:

- Upon request and for special quantities inserts can be supplied in different materials.
- Upon request and for special quantities available in the colours indicated in the chart [page].



Code	art.	D	H	d	m	c	A	B	d1 _{6H}	Q	g
H77318.0001	H7 7318 .TM 0 4 0 1	17.5	18	12	4	14	1.2	1.5	M4	7	6.5
H77318.0002	H7 7318 .T M 0 5 0 1	17.5	18	12	4	14	1.2	1.5	M5	7	7
H77318.0003	H7 7318 .T M 0 6 0 1	17.5	18	12	4	14	1.2	1.5	M6	7	7

H774

KNURLEDKNOB WITH SLOT END AND THREADED STUD



Materials:

Reinforced polyamide.
Resistant to oils and greases.

Surface finish:

Satin.

Colour:

Black (RAL9011).

Inserts:


Galvanised steel threaded stud (thread tolerance 6g).

Special Requests:

- Upon request and for special quantities inserts can be supplied with customised lengths.
- Upon request and for special quantities inserts can be supplied in different materials.
- Upon request and for special quantities available in the colours indicated in the chart [page].



08



Code	art.	D	H	d	m	c	A	B	LM	d1 _{6g}	Q	g
H77418.0003	H77418.TM04X3001	17.5	18	12	4	14	1.2	1.5	50	M4	3	7.5
H77418.0006	H77418.TM05X3001	17.5	18	12	4	14	1.2	1.5	60	M5	0	9
H77418.0009	H77418.TM06X3001	17.5	18	12	4	14	1.2	1.5	60	M6	3	11

LM = maximum mouldable length.

Threaded stud length on request, with a minimum quantity of 250 pieces.

0
3
0

W459HIN

NEW

+200°
-40°

Aisi
304
4

RoHS
COMPLIANT

STAINLESSSTEELKNURLED KNOB WITH THREADED HOLE

INOX

Materials:

Precision-caststainless steel, (Aisi 304).

Surface finish:



Electropolishedsatin finish.

Colour:

Natural.

Special requests:

- None.
- Femalethreadedhole (thread tolerance 6H).



INOX

Code	Art.	D	H	d	m	d1 _{6H}	Q	g
W459020.0001	W459020.HNM05HIN	20	13	14	4,5	M5	8	3
W459024.0001	W459024.HNM06HIN	24	15	16	4,5	M6	9	3
W459028.0001	W459028.HNM08HIN	28	17	18	4,5	M8	10	3

W460HIN NEW

STAINLESSSTEELKNURLED KNOB WITH THREADED STUD



INOX

Materials:

Knob:

Precision-cast stainless steel, (Aisi 304).

Stud:

Stainless steel (Aisi 303).

Surface finish:

Knob:

Electropolished satin finish.

Stud:

Smooth.

Colour:

Natural.


Inserts:

Turnedthreaded stud (thread tolerance 6g).


ATTENTION: The stud is fixed with glue.

Special requests:

- Uponrequest and for a minimum of 50 pieces inserts can be supplied with customised lengths.



08



INOX

Code	Art.	D	H	d	m	d1 _{6H}	Q	g
W460020.0001	W460020.HNM05X20HIN	20	13	14	4,5	M5	20	3
W460024.0002	W460024.HNM06X20HIN	24	15	16	4,5	M6	20	3
W460028.0001	W460028.HNM08X30HIN	28	17	18	4,5	M8	30	3

Customised stud length available for a minimum of 50 pieces.

W464

KNURLED METAL HANDWHEEL WITH THREADED STUD



C40

AISI
303

RoHS
COMPLIANT

Materials:

W464:

Steel with strength class 5.8.

W464CIN:

Stainless steel (Aisi 303).

Surface finish:

Turned with low roughness.

Colour:

W464:

Nickel plated (galvanic treatment).

W464 CIN:

Natural.

Alternative finishes:

Black-oxide treatment:

(replace the final letter of the code (H) with letter B (W46429.SM08X..B).

Galvanising:




(replace the final letter of the code (H) with letter Z (W46429.SM08X..Z).

Stud:

Threaded stud machined from solid metal (thread tolerance 6g).

Special requests:

- Upon request and for special quantities inserts can be supplied with customised lengths.



Version W464 - nickel-plated steel

Code	Art.	d	D	H	m	c	Q Max	d1 _{6g}	Q	g
W46411.0006	W46411.SM03X16H	6	11	8	5	3	16	M3	16	5
W46415.0002	W4 6 415. S M 0 4X10 H	8	15	10	6	4	20	M4	10	7.8
W46419.0005	W46419.SM05X16H	10	19	12	8	4	25	M5	16	15,6
W46423.0005	W46423.SM06X16H	12	23	15	10	5	35	M6	16	27,5
W4 6 423 . 0 010	W46423.SM06X35H	12	23	15	10	5	35	M6	35	30,5
W46429.0004	W4 6 429. S M 0 8X16 H	16	29	18	12	6	40	M8	16	55
W46429.0007	W46429.SM08X30H	16	29	18	12	6	40	M8	30	59
W46435.0004	W46435.SM10X25H	20	35	23	15	8	40	M10	25	109,5

Customised stud length available for a minimum of 100 pieces.
Q_{max} = maximum turning length.

Version W464 CIN - stainless steel (Aisi 303)

Code	Art.	d	D	H	m	c	Q Max	d1 _{6g}	Q	g
W46423.0002	W46423.IM06X35CIN	12	23	15	10	5	35	M6	35	30.5

Customised stud length available for a minimum of 100 pieces.
Q_{max} = maximum turning length.

INOX

W466

KNURLED METAL HANDWHEEL WITH THREADED HOLE



C40

AISI
303



Materials:

W466:

Steel with strength class 5.8.

W466 PIN:

Stainless steel (Aisi 303).

Surface finish:

Turned with low roughness.

Colour:

W466:

Nickel plated (galvanic treatment).

W466 PIN:

Natural.

Alternative finishes:

Black-oxide treatment:

(replace the final letter of the code (H) with letter B (W46629.SM08B)).

Galvanising:

(replace the final letter of the code (H) with letter Z (W46629.SM08Z)).

Hole:

Threaded through hole machined from solid metal (thread tolerance 6H).

Special requests:

- Upon request and for special quantities inserts can be supplied to customer's drawing with hole diameter d1.



08






ST. STEEL



Galvanised ver.



Black-oxide
treated ver.



Version W466 - nickel-plated steel

Code	Art.	d	D	H	m	c	d1 _{6H}	g
W46611.0003	W46611.SM03H	6	11	8	5	3	M3	3
W46615.0003	W46615.SM04H	8	15	10	6	4	M4	7
W46619.0002	W46619.SM05H	10	19	12	8	4	M5	12
W46623.0004	W46623.SM06H	12	23	15	10	5	M6	22.5
W46629.0003	W46629.SM08H	16	29	18	12	6	M8	45
W46635.0003	W46635.SM10H	20	35	23	15	8	M10	87
W46639.0004	W46639.SM12H	22	39	25	15	10	M12	121

Version W466 PIN - stainless steel (Aisi 303)

INOX

Code	Art.	d	D	H	m	c	d1 _{6H}	g
W46611.0001	W46611.IM03PIN	6	11	8	5	3	M3	3
W46615.0001	W46615.IM04PIN	8	15	10	6	4	M4	7
W46619.0001	W46619.IM05PIN	10	19	12	8	4	M5	12
W46623.0001	W46623.IM06PIN	12	23	15	10	5	M6	22.5
W46629.0001	W46629.IM08PIN	16	29	18	12	6	M8	45
W46635.0001	W46635.IM10PIN	20	35	23	15	8	M10	87
W46639.0002	W46639.IM12PIN	22	39	25	15	10	M12	121

W467



C40

Aisi
303
3



KNURLED METAL HANDWHEEL WITH SHORT HUB AND THREADED HOLE

Materials:

W4 67:
Steel with strength class 5.8.

W467 PIN:
Stainless steel (Aisi 303).

Surface finish:

Turned with low roughness.

Colour:

W4 67:
Nickel plated (galvanic treatment).

W467 PIN:
Natural.

Alternative finishes:


Black-oxide treatment:
(replace the final letter of the code (H) with letter B (W46729.SM08B).

Galvanising:
(replace the final letter of the code (H) with letter Z (W46729.SM08Z).

Hole:

Threaded through hole machined from solid metal (thread tolerance 6H).

Special requests:
Upon request and for special quantities inserts can be supplied to customer's drawing with hole diameter d1.



Version W467 - nickel-plated steel

Code	Art.	d	D	H	m	c	d1 _{6H}	g
W46711.0002	W46711.SM03H	6	11	3	0,5	3	M3	2
W46715.0002	W46715.SM04H	8	15	4	0,5	4	M4	5
W4 6719.0 0 0 2	W46719.SM05H	10	19	5	1	4	M5	9
W46723.0002	W46723.SM06H	12	23	6	1	5	M6	16
W46729.0002	W46729.SM08H	16	29	8	2	6	M8	32
W46735.0003	W46735.SM10H	20	35	10	2	8	M10	61
W46739.0002	W46739.SM12H	22	39	12	2	10	M12	92

Version W467 PIN - stainless steel (Aisi 303)

INOX

Code	Art.	d	D	H	m	c	d1 _{6H}	g
W4 6711.0 0 0 1	W46711.IM03PIN	6	11	3	0,5	3	M3	2
W4 6715.0 0 0 1	W46715.IM04PIN	8	15	4	0,5	4	M4	5
W4 6719.0 0 0 1	W46719.IM05PIN	10	19	5	1	4	M5	9
W4 6723.0 0 0 1	W46723.IM06PIN	12	23	6	1	5	M6	16
W46729.0001	W46729.IM08PIN	16	29	8	2	6	M8	32
W4 6735.0 0 0 1	W46735.IM10PIN	20	35	10	2	8	M10	61
W46739.0001	W46739.IM12PIN	22	39	12	2	10	M12	92

Y303

DIN6303-KNURLED THUMB KNOB WITH THREADED HOLE



Materials:

Y303:

Free-cutting steel.

Y303PIN:

Stainless steel (Aisi 303).

Surface finish:

Smooth, turned.

Colour:

Y303:

Black-oxide treatment.

Y303PIN:

Natural.

Hole:




Threadedthroughhole (thread tolerance 6H).

Special requests:

- None.



08



Version Y303: black-oxide treated steel

Code	Art.	D	d	H	m	c	d1 _{6H}	Q	g
Y303020.0002	Y303020.VBM05	20	14	12	4	8	M5	7	17
Y303024.0002	Y303024.VBM06	24	16	14	4	10	M6	8	30
Y303030.0002	Y303030.VBM08	30	20	17	5	12	M8	10	50
Y303036.0002	Y303036.VBM10	36	28	20	6	14	M10	12	90
Y303040.0002	Y303040.VBM12	40	32	24	8	16	M12	16	124

Version Y303 PIN: stainless steel (Aisi 303)

INOX

Code	Art.	D	d	H	m	c	d1 _{6H}	Q	g
Y303020.0001	Y303020.INM05PIN	20	14	12	4	8	M5	7	17
Y303024.0001	Y303024.INM06PIN	24	16	14	4	10	M6	8	30
Y303030.0001	Y303030.INM08PIN	30	20	17	5	12	M8	10	50
Y303036.0001	Y303036.INM10PIN	36	28	20	6	14	M10	12	90
Y303040.0001	Y303040.INM12PIN	40	32	24	8	16	M12	16	124

Y653



AVP

AISI
303
3

RoHS
COMPLIANT

DIN653-FULL STEEL DIAMOND KNURLED THUMB SCREW WITH THREADED DOME-END STUD

Materials:

Y653:
Free-cutting steel.

Y653 CIN:
Stainless steel (Aisi 303).

Surface finish:
Smooth, turned.


Colour:

Y653:
Black-oxide treatment.

Y653 CIN:
Natural.

Stud:

Threadedstudwith dome end (thread tolerance 6g).



Special requests:

- None.

Version Y653CIN - stainless steel (Aisi 303)

INOX

Code	art.	D	H	d1 _{6g}	Q	g
Y653012.0001	Y653012.INM03X06CIN	12	2,5	M3	06	3
Y653012.0002	Y653012.INM03X10CIN	12	2,5	M3	10	3
Y653016.0001	Y653016.INM04X10CIN	16	3,5	M4	10	6
Y653016.0002	Y653016.INM04X16CIN	16	3,5	M4	16	7
Y653020.0001	Y653020.INM05X10CIN	20	4	M5	10	11
Y653020.0002	Y653020.INM05X16CIN	20	4	M5	16	12
Y653020.0003	Y653020.INM05X25CIN	20	4	M5	25	14
Y653024.0001	Y653024.INM06X12CIN	24	5	M6	12	20
Y653024.0002	Y653024.INM06X16CIN	24	5	M6	16	21
Y653024.0003	Y653024.INM06X25CIN	24	5	M6	25	23
Y653024.0004	Y653024.INM06X30CIN	24	5	M6	30	24
Y653024.0005	Y653024.INM06X35CIN	24	5	M6	35	25
Y653030.0001	Y653030.INM08X16CIN	30	6	M8	16	37
Y653030.0002	Y653030.INM08X20CIN	30	6	M8	20	39
Y653030.0003	Y653030.INM08X25CIN	30	6	M8	25	40
Y653030.0004	Y653030.INM08X35CIN	30	6	M8	35	43
Y653030.0005	Y653030.INM08X40CIN	30	6	M8	40	48
Y653036.0001	Y653036.INM10X20CIN	36	8	M10	20	72
Y653036.0002	Y653036.INM10X30CIN	36	8	M10	30	76
Y653036.0003	Y653036.INM10X40CIN	36	8	M10	40	80

Version Y653: black-oxide treated steel

Code	art.	D	H	d1 _{6g}	Q	g
Y653012.0004	Y653012.VBM03X06	12	2,5	M3	06	3
Y653012.0005	Y653012.VBM03X10	12	2,5	M3	10	3
Y653016.0003	Y653016.VBM04X10	16	3,5	M4	10	6
Y653016.0004	Y653016.VBM04X16	16	3,5	M4	16	7
Y653020.0004	Y653020.VBM05X10	20	4	M5	10	11
Y653020.0005	Y653020.VBM05X16	20	4	M5	16	12
Y653020.0006	Y653020.VBM05X25	20	4	M5	25	14
Y653024.0007	Y653024.VBM06X12	24	5	M6	12	20
Y653024.0008	Y653024.VBM06X16	24	5	M6	16	21
Y653024.0009	Y653024.VBM06X25	24	5	M6	25	23
Y653024.0010	Y653024.VBM06X30	24	5	M6	30	24
Y653024.0011	Y653024.VBM06X35	24	5	M6	35	25
Y653030.0006	Y653030.VBM08X16	30	6	M8	16	37
Y653030.0007	Y653030.VBM08X20	30	6	M8	20	39
Y653030.0008	Y653030.VBM08X25	30	6	M8	25	40
Y653030.0009	Y653030.VBM08X35	30	6	M8	35	43
Y653030.0010	Y653030.VBM08X40	30	6	M8	40	48
Y653036.0004	Y653036.VBM10X20	36	8	M10	20	72
Y653036.0005	Y653036.VBM10X30	36	8	M10	30	76
Y653036.0006	Y653036.VBM10X40	36	8	M10	40	80